


EZ Deck Crane Folding Hydraulic Double Telescopic Crane 2,500 to 20,000lb 1,134 to 9070kg



Double Telescopic Folding Deck Crane

The folding crane system represents the innovation and thoughtful design that Nautical Structures brings to the challenge of creative tender-handling solutions. Developed for use on board a luxury sailing yacht, the folding davit's initial requirement was to live in an enclosed space under a deck hatch. Potentially a very wet, humid and corrosive environment for any machinery. The Folding Crane is constructed from aluminum alloy, utilizing composite bushings to eliminate the reaction of dissimilar metals. Our current designs begin at working load capacities of 800lb / 362kg, 1200lb/ 545kg, 1500lb/ 682kg and 4400lb/ 2000kg .Any of these cranes may be special-ordered built to MCA Mega Yacht Code / Classification Society compliance. This specification sheet describes our smaller cranes with lifting capacities of up to fifteen hundred pounds.

The Folding Crane's telescoping aluminum boom is capable of being loaded to its full safe working load capacity in any position without restriction. The intelligent engineering inherent in this design allows distributed loaddeflection across the boom during moments of dynamic loading, reducing the amount of shock-loading transmitted to the deck. Virtually silent-operating, our Hydraulic Linear Winch system, a totally non-fouling winch design reflects the innovative and dependably safe operating characteristics built into the extending boom. This feature adds the additional element of operational safety as the winch travels with the boom during operation of the crane. This prevents any possibility of two-blocking the system causing damage to the cable. The crane features 270° hydraulic power rotation. The crane is remotely operated with a wireless joy-stick operated proportional control provided with an optional-use removable pendant. A bearing platter is the typical mounting structure for the Folding Crane, although a pedestal base or a standpipe mount may also be used in some applications. The Folding Crane is powered by a hydraulic power unit, available in various horsepower configurations depending on the performance characteristics desired. The Folding Crane is finished to our highest standards. Depending on the anticipated mounting location, this davit system may be anodized, or finished in a high-quality urethane paint finish. The crane system is assembled and installed onto one of our three dynamic load-testing centers where our guality assurance team dynamic load tests and inspects every crane we produce prior to delivery to the customer. Warranty is 1-Year including materials, electrical, hydraulic and labor. See warranty for details.



MECHANICAL SPECIFICATIONS	ELECTRIC – HYDRAULIC SPECIFICATIONS
Hydraulic Boom Luffing: -45° to +30° full load capacity.	115/230V AC/60/50/1 .
Boom articulates 0° to + 89°	Wireless proportional control.
Aft rotation clearance:10in / 25cm270° hydraulic power rotation.180° and 360° is available.Hydraulic Linear Winch system.Rigged 6:1 with stainless steel wire	Motor Supply: 208-230/460V, 39-36/18A, 60/50Hz, 3-Ph 3.5 Hp HPU, 3000 psi / 203 bar, 1.5 gpm / 5 lpm output. 5.0 Hp HPU, 3000 psi / 203 bar, 2.5 gpm / 9 lpm output. 7.5 Hp HPU, 3000 psi / 203 bar, 3.5 gpm /13 lpm output. Fluid type: AW-68, ISO quality 17 /15/12
rope, stainless steel weight and stainless steel safety snap hook.	RATED CAPACITY
Cable pay-out: 26ft / 7.92m	FC-880: 880lb / 400kg Up to 12,000 ft/lb
Crane weight, FC-880:Avg.810lb / 368kgCrane weight, FC-1200:Avg.840lb / 382kgCrane weight, FC-1500:Avg.1050lb / 477kgMounting Platter weight:Avg.65lb / 30kg	FC-1200: 1,200lb / 546kg Up to 16,500 ft/lb FC-1500: 1,500lb / 682kg Up to 18,000 ft/lb FC-4400: 4,400lb / 2000kg Up to 80,000 ft/lb Other load capacities / moment load capacities are available
Standpipe Weight (average):650lb / 295kgWeight, pedestal base (average):340lb / 155kg	as a special order project. 12 Month limited warranty. © 2014 - NSI

7301 114th Avenue North • Largo, Florida 33773

Phone: (727) 541-6664 • Facsimile: (727) 541-6353 • North America Toll Free: (888) 541-6664 Email: sales@nautical-structures.com • www.nautical-structures.com